



الشركة اليمنية لصناعة الطلاء و مشتقاته المحدودة
Yemen Company for Paints & Derivatives Ltd.

ATLAS MULTI-PURPOSE GLUE



DESCRIPTION:

Atlas Multi-Purpose Glue is a high viscosity, high solid multipurpose PVA copolymer for various applications.

USES:

As multi-purpose glue for bonding wood to wood, paper to wood, paper to paper and paper to wall.

Technical Data

Product Type	Copolymer
Color	White
Finish variants	Translucent
Weight Solid	-
Specific Gravity	0.94-1.1 g/ml (Dependable on Color)
Viscosity @ 25°C	300-340 gm
Touch Dry	20 minutes @ 25°C
Thinner	Water
Theoretical Coverage	12 m ² / lt. for one coat. (Dependable on surface conditions & application methods)
Packs Offered	750gm
Shelf Life	2 years from the date of manufacture in original tightly closed containers away from direct sunlight and excessive heat.

Application Details

Thinning Volume Product is ready for use if thinning is required 25% max. is recommended.

Surface Preparation

Surface should sound, dry and clean from contamination, loose materials, oil and dust

For Further Information, please contact us at:

Yemen Company for Paints & Derivatives Ltd.

Tel. +967-4-205570/72

E-mail: info@ycpd.biz





الشركة اليمنية لصناعة الطلاء و مشتقاته المحدودة
Yemen Company for Paints & Derivatives Ltd.

Precautions

1. Kindly refer to MSDS for detailed safety measures while handling the paint.
2. Store the product in ambient conditions in well ventilated locations and away from source of ignition and fire.
3. Avoid eye and skin contact. In case it happens, wash with plenty of clean water.
4. Do not inhale or inject. In case of inhalation move to fresh air.
5. Use protective equipments like globes, safety glasses, face mask while handling the paint – this is required for all paint.
6. Do not apply when the ambient temperature is less than 10°C or it might drop to this level within 4 hours of application.
7. Both white and tinted paints need through shaking / mixing immediately before use.
8. Where ever dilution is necessary, use pure water. Adjust a viscosity of 30 – 40 sec for brush application and for other method use at 20 – 30 sec by Ford cup No. 4

Note: Data, specifications, directions and recommendations given in this data sheet represent only test results or experience obtained under controlled or specially defined circumstances. Their accuracy, completeness or appropriateness under the actual conditions of any intended use of the Products herein must be determined exclusively by the Buyer and/or User.

For Further Information, please contact us at:

Yemen Company for Paints & Derivatives Ltd.

Tel. +967-4-205570/72

E-mail: info@ycpd.biz

