



ATLAS SUPER PUTTY



DESCRIPTION:

Atlas Super Putty is vinyl acrylic water based putty. It is specially formulated for leveling of minor surface irregularities up to 3 – 4 mm.

USES:

It is used for filling blemishes, cracks, holes on masonry and patching up surface imperfections on plastered walls.

MAIN FEATURES:

- Excellent filling ability.
- It is only recommended for internal application.

Technical Data

Product Type	Vinyl Acrylic Copolymer Emulsion
Color	White
Finish variants	Smooth and Matt
Weight Solid	72 ± 1 %
Specific Gravity	1.73 ± 0.02
Viscosity @ 25°C	Min. 160,000 cps by Brookfield Viscometer
Flash Pont	It's not flammable
Thinner	Ready For Use
Theoretical Coverage	1.6 – 2.1 m ² / kg for one coat.
Packs Offered	20Kg, 4Kg (Gross)
Shelf Life	1 year from the date of manufacture in original tightly closed containers away from direct sunlight and excessive heat.

Recommended Applications

Apply using Trowel, Putty Knife and Leveler

Depending on the surface smoothness required, either one or 2 coats can be applied

For Further Information, please contact us at:

Yemen Company for Paints & Derivatives Ltd.

Tel. +967-4-205570/72

E-mail: info@ycpd.biz





Direction of use

Surface Preparation

Allow all new masonry surfaces to dry completely. Remove all loose or defective paint or powdery residue by scraping. Treat any areas affected by mould, lichens, algae and moss with 1% solution of Surface Treatment Chemical (STC.). Fill up minor cracks and defects with Atlas Super Putty after one coat of primer application. Allow to dry completely. Then sand with emery paper to smoothen the surface. The powders from sanding are to be wiped out completely. Then apply another coat of primer on the puttied surface. Apply primer in thin coats.

*: Recoating Interval was quoted for 28 – 30⁰C and at 60 – 65% Relative Humidity

Precautions

1. Kindly refer to MSDS for detailed safety measures while handling the paint.
2. Store the product in ambient conditions in well ventilated locations and away from source of ignition and fire.
3. Avoid eye and skin contact. In case it happens, wash with plenty of clean water.
4. Do not inhale or inject. In case of inhalation move to fresh air.
5. Use protective equipments like globes, safety glasses, face mask while handling the paint – this is required for all paint.
6. Do not apply when the ambient temperature is less than 10⁰C or it might drop to this level within 4 hours of application.
7. Premix the Putty uniformly before use.

Note: Data, specifications, directions and recommendations given in this data sheet represent only test results or experience obtained under controlled or specially defined circumstances. Their accuracy, completeness or appropriateness under the actual conditions of any intended use of the Products herein must be determined exclusively by the Buyer and/or User.

For Further Information, please contact us at:

Yemen Company for Paints & Derivatives Ltd.

Tel. +967-4-205570/72

E-mail: info@ycpd.biz

