



## WOOD GLUE

**Description:** A PVA co-polymer based high viscosity high solid wood glue which dries to a hard translucent film resistant to water.

**Uses:** A multi-purpose glue for wood bonding in furniture, doors, windows and wooden frames.

### Physical Properties

**Color :** White  
**Finish:** Translucent  
**Touch dry :** 20 minutes @ 25° C  
**Pack Sizes:** 500g / 4kg / 15kg / 125kg  
**Thinner / cleaning agent :** water

### Application Details

**Application method:** Brush  
**Thinning volume:** Product is ready for use if thinning is required 30% max. is recommended.

**Surface Preparation:** Surface should sound, dry and clean from contamination, loose materials, oil and dust

**Remarks:** Shelf life of the product is 12 months

**Safety:** Handle with care: Strictly follow the handling, storage and use instruction on paint containers and/or MSDS including the personal protection during application by taking all the necessary precautions for the protection of lungs, eyes and skin, medical treatment in case of swallowing: Apply in well ventilated areas.

The above information is based on our best knowledge and laboratory test. Result may vary according to the working conditions, substrate properties and application system

---

*For Further Information, please contact us at:*  
**Yemen Company for Paints & Derivatives Ltd.**

**Tel. +967-4-205570/72**

**E-mail: [info@yepd.biz](mailto:info@yepd.biz)**

