

# ATLAS GROUT (TARWEBA)

## DESCRIPTION:

*Tarweba*, is a high performance cementations non - shrink grout, based on white cement modified polymer. It is manufactured using high quality fine fillers to improve ease of finishing.



## USES:

*Tarweba* is suitable for use with glazed and unglazed tiles and has excellent adhesion to all tile types. It is water and mold resistant and is suitable use in kitchens, bathrooms and shower enclosures.

## FEATURES:

- Good Compressive, Flexural Strength along with good abrasion Resistance.
- It mixes easily with water to a lump-free paste which can provides smooth finish.
- When mixed has a working time of 60 minutes.

## PRODUCT INFORMATION:

Appearance	Free Flowing Powder
Colour	White
Mass Solid	100 %
Specific Gravity	2.6 (Typical)
Application Temp.	5°C - 35°C
Drying Time (Hard Dry)	24 Hours
Pot Life	Approx. 1 Hours
Coverage	Depends on the size of Tile, Joint Width & Depth. (Approx 0.25 Kg/ m <sup>2</sup> for 200 x 150mm tile 3 mm deep, at 2 mm wide joint)

## APPLICATION DETAILS

### • Mixing:

The grout should be added to clean water and mixed to a thick creamy consistency at approximately 2 parts of powder to one part of water (by weight). Allow to stand for 3-5 minutes, and then mix again. The mixed grout is usable for up to 60 minutes depending on site temperature and conditions. Do not add extra water as this will cause a loss in performance.

*For Further Information, please contact us at:*

**Yemen Company for Paints & Derivatives Ltd.**

Tel. +967-4-205570/72

E-mail: [info@ycpd.biz](mailto:info@ycpd.biz)



- **Method:**

Apply the grout to the joints with a grouting trowel, squeegee or sponge, ensuring that the joints are completely filled. Compact the grout in the joints and clean off excess with a damp cloth or sponge as the grouting proceeds. Allow the grout to harden sufficiently to prevent removal from the joints when cleaning. This hardening will usually occur within 1-2 hours.

- **Surface Preparation:**

Ensure the tile adhesive is sufficiently cured prior to commencing grouting. Allow a minimum of 24 hours when using standard setting adhesives and ready mixed tile adhesives or 2 - 3 hours when using fast setting adhesives. Ensure that the joints are clean and dust free and are a maximum of 4mm wide.

---

*For Further Information, please contact us at:*

**Yemen Company for Paints & Derivatives Ltd.**

**Tel. +967-4-205570/72**

**E-mail: [info@ycpd.biz](mailto:info@ycpd.biz)**

