



Product code : 117-3

CROWN SEMI-GLOSS

Description: A durable odourless lead-free alkyd based enamel with excellent flow and leveling properties. It dries to a smooth and hard weather resisting coating over correctly primed surfaces.

Uses: A finishing coat on alkyd paint systems for interior or exterior surfaces (steel , wood, masonry...etc) in domestic or commercial facilities and in mild industrial environment where a 50% gloss finish is required

Physical Properties

Colors / Shades:	White (Other colors available as per color card)
Finish:	Semi- Gloss
Theoretical Spreading Rate:	13 m ² / liter (depend able on surface conditions and application method)
Touch dry :	4 - 6 hour @ 25° C
Pack Sizes:	3.5 liter : 17 liter
Thinner / cleaning solvent :	Atlas Thinner : Turpentine

Application Details

Application method:	Airless spray, Air Spray, Brush or Roller
Thinning volume:	10% - 25 %
Re-Coating Interval:	Minimum 16 hours

Preceding Coat :	Steel : Red Oxide primer / Zinc Phosphate primer Concrete / Wood : Alkyd Undercoat
------------------	---

Surface Preparation	Concrete : surface should sound, dry and clean from contamination, loose materials, oil and dust. Cracks should be filled with correct filler. New steel : Should be clean, free of oil, grease, rust and dust residues. Maintenance: loose Old paint must be removed thoroughly. Remove oil and grease. Remove salt and contamination.
---------------------	--

Remarks :	FLAMMABLE
-----------	-----------

Safety

Handle with care: Strictly follow the handling, storage and use instruction on paint containers and/or MSDS including the personal protection during application by taking all the necessary precautions for the protection of lungs, eyes and skin, medical treatment in case of swallowing: Apply in well ventilated areas.

The above information is based on our best knowledge and laboratory test. Result may vary according to the working conditions, substrate properties and application system

