



GLOBE TEXTURE

Description: A water based attractive coating containing granular texture with good adhesion and perfect weather resistance. Different patterns can be achieved using different application methods.

Uses: A topcoat suitable for decoration of interior and exterior surfaces such as cement, concrete, walls, partitions ...etc

Physical Properties

Colors / Shades: White *
Finish: Matt with fine or medium granules
Theoretical Spreading Rate: 2 m²/ kg (depend able on surface conditions and application method)
Surface dry : 30 minutes @ 25° C
Pack Sizes: 20 kg
Thinner / cleaning solvent : Water
* Other shades available on request as per color card

Application Details

Application method: Spray Gun , Roller
Thinning volume: 10%
Re-Coating Interval: Minimum 6 hours
Preceding Coat : Crown Sealer / Atlas Emulsion

Surface Preparation
Concrete : surface should sound, dry and clean from contamination, loose materials, oil and dust. Cracks should be filled with correct filler.
Maintenance : loose Old paint must be removed thoroughly. Remove oil and grease. Remove salt and contamination.

Safety

Handle with care: Strictly follow the handling, storage and use instruction on paint containers and/or MSDS including the personal protection during application by taking all the necessary precautions for the protection of lungs, eyes and skin, medical treatment in case of swallowing: Apply in well ventilated areas.

The above information is based on our best knowledge and laboratory test. Result may vary according to the working conditions, substrate properties and application system

for further information, please contact our technical department at :

Yemen Company For Paints & Derivatives Ltd.

Tel. +967 4 205570 / 72 e-mail : ycpd@y.net.ye

